

PRODUCT-DETAILS

## T16-2.3

### T16-2.3 Thermal Overload Relay



#### Información General

|                            |   |
|----------------------------|---|
| Tipo de producto extendido | T16-2.3   |
| Código de producto         | 1SAZ711201R1031   |
| EAN                        | 4013614397905   |
| Descripción corta          | T16-2.3 Thermal Overload Relay  |
| Descripción larga          | <p>The T16-2.3 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the mini contactors or block contactors. Single mounting kits are available as accessory.</p> |

#### Clasificación

|                           |          |
|---------------------------|----------|
| Cantidad mínima de pedido | 1 piece  |
| Código arancelario        | 85364900 |

#### Descargas Populares

|                                    |                                    |
|------------------------------------|------------------------------------|
| Ficha técnica, información técnica | 2CDC106020D0201                    |
| Instrucciones y manuales           | 2CDC106019M6802<br>2CDC106021M6801 |
| Time-Current Characteristic Curve  | 1SAZ700505F0011                    |

## Dimensiones

|                   |         |
|-------------------|---------|
| Ancho del product | 45 mm   |
| Alto del producto | 76.7 mm |
| Largo del product | 53.5 mm |
| Peso del product  | 0.1 kg  |

## Technical

|  |   |
|--|---|
| Setting Range  | 1.7 ... 2.3 A   |
| Rated Operational Voltage                                | Auxiliary Circuit 600 V AC/DC<br>Main Circuit 690 V AC  |
| Rated Operational Current (I <sub>e</sub> )              | 2.3 A   |
| Rated Operational Current AC-3 (I <sub>e</sub> )         | 2.3 A   |
| Rated Frequency (f)                                      | Auxiliary Circuit 50 Hz<br>Auxiliary Circuit 60 Hz<br>Auxiliary Circuit DC<br>Main Circuit 50 Hz<br>Main Circuit 60 Hz  |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )      | Auxiliary Circuit 6 kV<br>Main Circuit 6 kV   |
| Rated Insulation Voltage (U <sub>i</sub> )               | 690 V   |
| Number of Poles  | 3   |
| Number of Auxiliary Contacts NC                          | 1   |
| Number of Auxiliary Contacts NO                          | 1   |
| Number of Protected Poles                                | 3   |
| Conventional Free-air Thermal Current (I <sub>th</sub> ) | Auxiliary Circuit NC 6 A<br>Auxiliary Circuit NO 4 A  |
| Rated Operational Current AC-15 (I <sub>e</sub> )        | (120 V) NC 3 A<br>(120 V) NO 0.5 A<br>(240 V) NC 3 A<br>(240 V) NO 0.5 A<br>(400 V) NC 0.75 A<br>(400 V) NO 0.5 A<br>(500 V) NC 0.75 A<br>(500 V) NO 0.5 A  |
| Rated Operational Current DC-13 (I <sub>e</sub> )        | (125 V) NC 0.55 A<br>(125 V) NO 0.55 A<br>(24 V) NC 1.25 A<br>(24 V) NO 1.25 A<br>(250 V) NC 0.27 A<br>(250 V) NO 0.27 A<br>(500 V) NC 0.15 A<br>(500 V) NO 0.15 A<br>(60 V) NC 0.55 A<br>(60 V) NO 0.55 A  |
| Grado de protección                                      | IP20  |
| Pollution Degree   | 3   |
| Connecting Capacity Auxiliary Circuit                    | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible 1/2x 0.75 ... 1 mm <sup>2</sup><br>Flexible 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid 1/2x 0.75 ... 4 mm <sup>2</sup> |
| Connecting Capacity Main Circuit                         | Flexible with Ferrule 1/2x 0.75 ... 4 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2x 0.75 ... 4 mm <sup>2</sup>  |

|                          |  |
|--------------------------|--|
|                          | Flexible 1/2x 0.75 ... 4 mm <sup>2</sup><br>Solid 1/2x 0.75 ... 1.5 mm <sup>2</sup><br>Solid 1/2x 1.5 ... 4 mm <sup>2</sup><br>Stranded 1/2x 1 ... 4 mm <sup>2</sup> |
| Tightening Torque        | Auxiliary Circuit 1 ... 1.2 N·m<br>Main Circuit 1.1 ... 1.5 N·m  |
| Wire Stripping Length    | Auxiliary Circuit 9 mm<br>Main Circuit 12 mm   |
| Recommended Screw Driver | Main Circuit Pozidriv 2  |
| Power Loss               | at Rated Operating Conditions per Pole 1.1 W   |
| Suitable For             | B6<br>BC6<br>B7<br>BC7<br>VB6<br>VBC6<br>VB7<br>VBC7<br>AS09<br>AS12<br>AS16   |
| Standards                | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>IEC/EN 60947-5-1<br>UL 60947-1<br>UL 60947-4-1   |

## Technical UL/CSA

|  |   |
|--|---|
| Maximum Operating Voltage UL/CSA             | Main Circuit 600 V AC   |
| Ampere Rating UL/CSA                         | 2.3 A   |
| Contact Rating UL/CSA                        | (NC:) B600<br>(NC:) Q600<br>(NO:) Q600<br>(NO:) D300            |
| Connecting Capacity Main Circuit UL/CSA      | Flexible 1/2x 18-12 AWG<br>Stranded 1/2x 18-10 AWG              |
| Connecting Capacity Auxiliary Circuit UL/CSA | Flexible 1/2x 18-12 AWG<br>Stranded 1/2x 18-12 AWG              |
| Tightening Torque UL/CSA                     | Auxiliary Circuit 9 ... 11 in·lb<br>Main Circuit 9 ... 13 in·lb |

## Ambiente

|  |  |
|--|--|
| Temperatura ambiente                           | Funcionamiento -25 ... +60 °C<br>Operation Compensated -25 ... +60 °C<br>Almacenamiento -50 ... +80 °C |
| Ambient Air Temperature Compensation           | Yes  |
| Maximum Operating Altitude Permissible         | 2000 m   |
| Resistance to Shock acc. to IEC 60068-2-27     | 11 ms Pulse 22g  |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 3g / 3 ... 150 Hz  |
| RoHS Status                                    | Following EU Directive 2011/65/EU  |

## Certificados y Declaraciones (Número de Documento)

|                 |                 |
|-----------------|-----------------|
| ABS Certificate | 1SAA941001-0102 |
| BV Certificate  | 1SAA941001-0203 |

|                                   |                                    |
|-----------------------------------|------------------------------------|
| CB Certificate                    | 1SAA941008-2001                    |
| CQC Certificate                   | CQC2011010309459316                |
| cUL Certificate                   | cUL_E48139                         |
| Declaration of Conformity - CCC   | 2020980304001787                   |
| Declaración de conformidad - CE   | 1SAD938510-0182                    |
| DNV GL Certificate                | 1SAA941001-0302                    |
| EAC Certificate                   | 1SAA941002-2702                    |
| Environmental Information         | 1SAC200055H0009                    |
| GL Certificate                    | 1SAA941007-0401                    |
| GOST Certificate                  | 1SAA941000-2704                    |
| Instrucciones y manuales          | 2CDC106019M6802<br>2CDC106021M6801 |
| LR Certificate                    | 1SAA941001-0502                    |
| RINA Certificate                  | 1SAA941000-0802                    |
| RMRS Certificate                  | 1SAA941000-0704                    |
| RoHS Information                  | 1SAD938507-0182                    |
| Time-Current Characteristic Curve | 1SAZ700505F0011                    |
| UL Certificate                    | UL_E48139                          |

## Información de Embalaje

|                                |               |
|--------------------------------|---------------|
| Embalaje Nivel 1 Unidades      | 1 piece       |
| Embalaje Nivel 1 Ancho         | 48 mm         |
| Embalaje Nivel 1 Alto          | 63 mm         |
| Embalaje Nivel 1 Largo         | 82 mm         |
| Embalaje Nivel 1 Peso          | 0.112 kg      |
| Embalaje Nivel 1 EAN           | 4013614397905 |
| Package Level 2 Units          | 40 piece      |
| Package Level 2 Width          | 280 mm        |
| Package Level 2 Height         | 210 mm        |
| Package Level 2 Depth / Length | 395 mm        |
| Package Level 2 Gross Weight   | 8.45 kg       |
| Package Level 2 EAN            | 4013614440618 |

## Clasificaciones

|                                    |                                   |
|------------------------------------|-----------------------------------|
| Object Classification Code         | F                                 |
| ETIM 4                             | EC000106 - Thermal overload relay |
| ETIM 5                             | EC000106 - Thermal overload relay |
| ETIM 6                             | EC000106 - Thermal overload relay |
| ETIM 7                             | EC000106 - Thermal overload relay |
| eClass                             | V11.0 : 27371501                  |
| UNSPSC                             | 39121520                          |
| IDEA Granular Category Code (IGCC) | 5364 >> Overload relay            |
| E-Number (Finland)                 | 3706143                           |
| E-Number (Sweden)                  | 3212064                           |

## Accessories

| Identifier      | Description                 | Type     | Quantity | Unit Of Measure |
|-----------------|-----------------------------|----------|----------|-----------------|
| 1SAZ701901R0001 | DB16 Single Mounting Kit    | DB16     | 1        | piece           |
| 1SFA616162R1014 | KPR3-101L Reset push button | KPR-101L | 1        | piece           |

---

## Categorías

---

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Relés térmicos

