



Accesorios de latón niquelado

Reducciones de rosca



- Fabricada en latón niquelado
- Rosca métrica EN 60423 i Pg DIN 40430
- Temperatura de trabajo: de -40°C a +100°C

Referencia	Rosca macho	Rosca hembra	Longitud rosca / mm	Ttipo	Envase u.
851612	M16 x 1,5	M12 x 1,5	7	3	100
852012	M20 x 1,5	M12 x 1,5	7	3	100
852016	M20 x 1,5	M16 x 1,5	7	3	100
852516	M25 x 1,5	M16 x 1,5	7	3	100
852520	M25 x 1,5	M20 x 1,5	8	3	100
853220	M32 x 1,5	M20 x 1,5	8	4	50
853225	M32 x 1,5	M25 x 1,5	8,5	3	50
854025	M40 x 1,5	M25 x 1,5	8	4	25
854032	M40 x 1,5	M32 x 1,5	8,5	1	20
855032	M50 x 1,5	M32 x 1,5	10	4	10
855040	M50 x 1,5	M40 x 1,5	9	4	10
856340	M63 x 1,5	M40 x 1,5	10	4	10
856350	M63 x 1,5	M50 x 1,5	10	4	10

090704	Pg 9	Pg 7	6	3	100
110704	Pg 11	Pg 7	6	3	100
110904	Pg 11	Pg 9	6	3	100
130904	Pg 13,5	Pg 9	6,5	3	100
131104	Pg 13,5	Pg 11	6,5	3	100
160904	Pg 16	Pg 9	6,5	3	100
161104	Pg 16	Pg 11	6,5	3	100
161304	Pg 16	Pg 13,5	6,5	3	100
211104	Pg 21	Pg 11	7	3	100
211304	Pg 21	Pg 13	7	3	50
211604	Pg 21	Pg 16	7	3	50
291604	Pg 29	Pg 16	8	4	50
292104	Pg 29	Pg 21	8	3	20
362104	Pg 36	Pg 21	9	4	25
362904	Pg 36	Pg 29	9	4	25
423604	Pg 42	Pg 36	10	4	10
482984 *	Pg 48	Pg 29	10	3	1
483684	Pg 48	Pg 36	10	4	10
484284	Pg 48	Pg 42	10	4	10

*disponibles hasta agotar stock