

Accesorios de latón niquelado

Adaptadores de rosca macho métrica a hembra Pg



| Referencia | Rosca macho | Rosca hembra | Longitud rosca / mm | Tipo | Envase u. |
|------------|-------------|--------------|---------------------|------|-----------|
| 801207 | M12 x 1,5 | Pg 7 | 7 | 1 | 50 |
| 801209 | M12 x 1,5 | Pg 9 | 7 | 1 | 50 |
| 801609 | M16 x 1,5 | Pg 9 | 7 | 1 | 50 |
| 801611 | M16 x 1,5 | Pg 11 | 7 | 1 | 50 |
| 802011 | M20 x 1,5 | Pg 11 | 7 | 1 | 50 |
| 802013 | M20 x 1,5 | Pg 13,5 | 7 | 1 | 50 |
| 802016 | M20 x 1,5 | Pg 16 | 7 | 1 | 50 |
| 902513 | M25 x 1,5 | Pg 13 | 8 | 3 | 20 |
| 902516 | M25 x 1,5 | Pg 16 | 8 | 1 | 20 |
| 802521 | M25 x 1,5 | Pg 21 | 8 | 1 | 20 |
| 903216 | M32 x 1,5 | Pg 16 | 8,5 | 3 | 20 |
| 903221 | M32 x 1,5 | Pg 21 | 8,5 | 1 | 20 |
| 803229 | M32 x 1,5 | Pg 29 | 8,5 | 1 | 20 |
| 904021 | M40 x 1,5 | Pg 21 | 8 | 3 | 20 |
| 904029 | M40 x 1,5 | Pg 29 | 8 | 1 | 20 |
| 804036 | M40 x 1,5 | Pg 36 | 8 | 1 | 20 |
| 805036 | M50 x 1,5 | Pg 36 | 9 | 2 | 10 |
| 805042 | M50 x 1,5 | Pg 42 | 9 | 2 | 5 |
| 906336 | M63 x 1,5 | Pg 36 | 10 | 4 | 10 |
| 906342 | M63 x 1,5 | Pg 42 | 10 | 4 | 10 |
| 806348 | M63 x 1,5 | Pg 48 | 10,5 | 1 | 5 |

- Fabricado en latón niquelado
- Rosca métrica EN 60423 i Pg DIN 40430
- Temperatura de trabajo: de -40°C a +100°C

Adaptadores de rosca macho Pg a hembra métrica



| Referencia | Rosca macho | Rosca hembra | Longitud rosca / mm | Tipo | Envase u. |
|------------|-------------|--------------|---------------------|------|-----------|
| 800712 | Pg 7 | M12 x 1,5 | 6,5 | 1 | 1 |
| 800916 | Pg 9 | M16 x 1,5 | 6,5 | 1 | 1 |
| 801116 | Pg 11 | M16 x 1,5 | 7 | 3 | 1 |
| 801320 | Pg 13,5 | M20 x 1,5 | 7 | 1 | 1 |
| 901620 | Pg 16 | M20 x 1,5 | 6,5 | 4 | 1 |
| 801625 | Pg 16 | M25 x 1,5 | 7 | 1 | 1 |
| 902125 | Pg 21 | M25 x 1,5 | 7 | 4 | 1 |
| 802132 | Pg 21 | M32 x 1,5 | 8 | 1 | 1 |
| 802940 | Pg 29 | M40 x 1,5 | 8,5 | 1 | 1 |
| 803650 | Pg 36 | M50 x 1,5 | 8,5 | 1 | 1 |
| 804263 | Pg 42 | M63 x 1,5 | 10 | 1 | 1 |

- Fabricado en latón niquelado
- Rosca métrica EN 60423 i Pg DIN 40430
- Temperatura de trabajo: de -40°C a +100°C

Dimensiones en mm.