

LEVI2070D



Model		LEVI2070D	
General	Screen Size	7 Inch	
	Resolution	800*480	
	Colors	260k colors	
	Brightness	300cd/m ²	
	Backlight Type	LED	
	Touch Screen	High precision four-wire resistive	
	Backlight Life Time	5,0000 hours	
	CPU	32-bits 300MHz RISC	
	Storage	128M FLASH + 128M DDRAM	
	USB Port	USB host + USB Client	
	COM (2 in 1)	COM1	RS422/RS485
		COM2	RS232
	Power	Power	<5w
		Power Supply	DC 24V (12~28V DC)
Dimension	Shell	PC+ABS, Cold Grey	
	Dimension (mm)	201.0W*147.0H*39.0D	
	Mounting size (mm)	192.0W*138.0H	
	Net/Gross (KG)	0.5/0.74	
Operate Environment	Temperature	Working Temperature : -10~60°C ; Storage Temperature : -20~70°C	
	Humidity	10-85%RH (Non-condensing)	
	Seismic Resistance	10~25 Hz (X,Y,Z direction 2G/30 minutes)	
	Cooling	Air cooling	
Protection		IP65 (Front panel)	
CE Certification		CE Certification: CE marked	
FCC Certification		FCC Class A	



LEVI2070D

