



General	Brightness	400cd/m ²	
	Backlight Type	LED	
	Touch Screen	High precision four-wire resistive	
	Backlight Life Time	50000 hours	
	CPU	32-bits 300MHz RISC	
	Storage	128M FLASH + 128M DDRAM	
	RTC	256KB	
	Printer Port	Serial port Printer	
	USB Port	USB host + USB Client	
	SD card	--	
COM	COM1	RS422/RS485	RS422/RS485
	COM2	RS232	RS232
	COM3	--	--
Power	Power	<5w	<5w
	Power Supply	DC 24V (12~28V DC)	
	Allowed Power Fail	<5ms	
	Insulation Resistance	>20MΩ 500V DC	
	Withstand Voltage	500V AC < 1 minute	
	Shell	ABS,Black	
Dimension	Dimension (mm)	96.0W*81.0H*33.0D	141.4W*85.4H*38.9D
	Mounting size (mm)	91.0W*73.0H	131.0W*79.0H
	Net/Gross (KG)	0.14/0.26	0.23/0.39
	Temperature	Working Temperature : -10~60°C ; Storage Temperature : -20~70°C	
Operate Environment	Humidity	Working Humidity : 10~90% RH ; Storage Humidity : 10~90%RH	
	Seismic Resistance	10~25 Hz (X,Y,Z direction 2G/30 minutes)	
	Cooling	Air cooling	
	Extension	Ethernet	--
CAN		--	--
TTS		--	--
COM3		--	--
Protection	IP65 (Front panel)		
CE Certification	CE Certification: CE marked		
FCC Certification	FCC Class A		