

Data sheet

Commercial Art.No.: 83.036.1010.0

Bus coupler unit RICOS FLEX BC PROFINET

ricos FLEX bus coupler PROFINET, 100Mbit/s, 512 byte input-output data, dimension (WxHxD): 48,5 x 109 x 76,5 mm, degree of protection IP20, DIN rail mounting, supply voltage: 20,4 -28,8V DC, type: ricos FLEX BC PROFINET



Commercial Art.No.	83.036.1010.0
EAN	4049088239588
Order Unit	1

Certificates / Approvals



Technical data

Technical data

Input voltage DC min.	20.4 V
Input voltage DC max.	28.8 V
Input current, max.	0.95 A
Baud rate max.	100 Mbit/s
Address range for inputs	512 Byte
Address range for outputs	512 Byte
Fieldbus connection	2 x RJ45 / Ethernet 100MBit
Fieldbus	PROFINET
Operating temperature min.	0 °C
Operating temperature max.	60 °C
Mounting method	DIN rail (top hat rail)
Weight	155 g
Terminal type	Spring-clamb connection
Terminal cross-section min.	0.08 mm ²
Terminal cross-section max.	1.5 mm ²

Abmessungen

Width	48.5 mm
Height	109 mm
Depth	76.5 mm

Classification

ETIM 7.0	EC001603
ETIM 6.0	EC001603
ETIM 4.0	EC001603
ETIM 3.0	EC001603