DATASHEET - ZP-NHK



Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, 2W, 0.5HP



Part no. Catalog No. EL-Nummer (Norway)

ZP-NHK 248437

r 0001609489

Delivery program

Basic function	Accessories for combined residual-current/power circuit-breakers Accessories for miniature circuit-breaker
Basic function accessories	Tripping signal contacts
Application	Switchgear for industrial and advanced commercial applications
Product range	Accessory
Side mounting	for fitting on left to: LS, FI/LS
Contact sequence	4.12/4.14 4.14/4.12 4.11 1.11 1.11 1.14 1.12

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-5
Operating ambient temperature max.	°C	40

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)

Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])

Device fitting		Universal
Additional equipment		Signalling switch
Attached at delivery		No
Assembly width (TE)		0.5
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		2
Number of fault-signal switches		0
Rated switch current	А	4
Rated voltage	V	250
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	А	4

