

PRODUCT-DETAILS

CAF6-20E

CAF6-20E Auxiliary Contact



Información General

Tipo de producto extendido	CAF6-20E
Código de producto	GJL1201330R0006
EAN	4013614148378
Descripción corta	CAF6-20E Auxiliary Contact
Descripción larga	The CAF6-20E is an auxiliary contact for front mounting with 2 auxiliary contact and screw terminals.

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85365080

Descargas Populares

Ficha técnica, información técnica	1SBC100214C0201
Instrucciones y manuales	2CDC102005M0101
Instructions and Manuals (Part 2)	2CDC102005M0101
Dimension Diagram	GJL1200446F0001

Dimensiones

Ancho del product	47.5 mm
Alto del producto	29 mm
Largo del product	26.5 mm
Peso del product	0.02 kg

Technical

Rated Operational Voltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 250 V DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U_{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U_i)	690 V
Grado de protección	IP20
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
Tightening Torque	Auxiliary Circuit 0.8 ... 1.1 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	0
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Conventional Free-air Thermal Current (I_{th})	Auxiliary Circuit 6 A
Product Name	Auxiliary Contact
Suitable For	B6-40-00 BC6-40-00 B7-40-00 BC7-40-00 VB6-40-00 VBC6-40-00 VB7-40-00 VBC7-40-00 VB6A-40-00 VBC6A-40-00 VB7A-40-00 VBC7A-40-00
Suitable for Product Class	Mini Contactors

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 600 V AC/DC
Connecting Capacity Auxiliary Circuit UL/CSA	Stranded 1/2x 22-10 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 in·lb

Contact Rating UL/CSA

A600

Ambiente

Temperatura ambiente	Funcionamiento -25 ... +55 °C Almacenamiento -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 5 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

Certificados y Declaraciones (Número de Documento)

CQC Certificate	CQC2003010304064035
cULus Certificate	cUL_E48139
Declaration of Conformity - CCC	2020980304001309
Declaración de conformidad - CE	1SAD938517-0001
Declaration of Conformity - UKCA	1SAD938500-1001
EAC Certificate	1SAA938002-2701
Instrucciones y manuales	2CDC102005M0101
Instructions and Manuals (Part 2)	2CDC102005M0101
RMRS Certificate	1SAA938001-0704
RoHS Information	1SAD938517-0001
UL Certificate	UL_E48139

Información de Embalaje

Embalaje Nivel 1 Ancho	115 mm
Embalaje Nivel 1 Largo	280 mm
Embalaje Nivel 1 Alto	54 mm
Embalaje Nivel 1 Peso	0.24 kg
Embalaje Nivel 1 EAN	4013614412271
Embalaje Nivel 1 Unidades	10 piece

Clasificaciones

Object Classification Code	K
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
E-Number (Finland)	3709097

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Mini Contactors Accessories

